

# Recursion

## Model 1 Factorial Function

"In mathematics, the factorial of a non-negative integer  $n$ , denoted by  $n!$ , is the product of all positive integers less than or equal to  $n$ . For example,  $5! = 5 \times 4 \times 3 \times 2 \times 1 = 120$ ."

Source: <https://en.wikipedia.org/wiki/Factorial>

$n$	$n!$
0	1
1	1
2	2
3	6
4	24
5	120

1. Consider how to calculate  $4! = 24$ .

a) Write out all the numbers that need to be multiplied:

$$4! = 4 * 3 * 2 * 1$$

b) Rewrite the expression using  $3!$  instead of  $3 \times 2 \times 1$ :

$$4! = 4 * 3!$$

2. Write expressions similar to #1b showing how each factorial can be calculated in terms of a smaller factorial. Each answer should end with a factorial (!).

a)  $2! = 2 * 1!$

b)  $3! = 3 * 2!$

c)  $100! = 100 * 99!$

d)  $n! = n * (n - 1)!$

3. What is the value of  $0!$  based on Model 3? Does it make sense to define  $0!$  in terms of a simpler factorial? Why or why not?

$0!$  is 1 (by convention for an empty product). We can't say  $0 \times -1!$ , because factorial is only defined for non-negative integers. At some point we need to define the solution in concrete terms, without referencing itself.

If we repeatedly break down a problem into smaller versions of itself, we eventually reach a basic problem that can't be broken down any further. Such a problem, like  $0!$ , is referred to as the **base case**.

4. Consider the following Python function that takes  $n$  as a parameter and returns  $n!$ :

```
1 def factorial(n):
2     # base case
3     if n == 0:
4         return 1
5     # general case
6     product = 1
7     for i in range(n, 0, -1):
8         product *= i
9     return product
```

a) Review your answer to #2c that shows how to compute  $100!$  using a smaller factorial. Convert this expression to Python by using the function above instead of the  $!$  operator.

```
100 * factorial(99)
```

b) Now rewrite your answer to #2d in Python using the variable  $n$  and the function above.

```
n * factorial(n - 1)
```

c) In the source code above, replace the "1" on Line 6 with your answer from b). Then cross out Lines 7 and 8. Test the resulting function in a Python Shell. Does it still work?

```
Yes, amazingly.
```

d) What specific function is being called on Line 6?

```
The factorial function that is being defined.
```

e) Why is the `if` statement required on Line 3?

```
Without the base case, it would call itself forever (until running out of memory).
```

5. A function that refers to itself is called **recursive**. What two steps were necessary to define the recursive version of `factorial`?

1. Write the base case, which was implemented using an `if` statement.
2. Write the recursive case, which was implemented using a function call.

6. Was a loop necessary to cause the recursive version of `factorial` to run multiple times? Explain your reasoning.

```
No; the function keeps calling itself until the base case is reached. The for loop was removed when we added the recursive call.
```

## Model 2 Fibonacci Numbers

The Fibonacci numbers are a sequence where every number (after the first two) is the sum of the two preceding numbers: 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, ...

Source: [https://en.wikipedia.org/wiki/Fibonacci\\_number](https://en.wikipedia.org/wiki/Fibonacci_number)

We can define a recursive function to compute Fibonacci numbers. Enter the following code into a Python Editor, and run the program to see the sequence.

```
1 def fibonacci(n):
2     # base case
3     if n == 1 or n == 2:
4         return 1
5     # general case
6     return fibonacci(n - 1) + fibonacci(n - 2)
7
8 def main():
9     for i in range(1, 6):
10        print(fibonacci(i))
11
12 main()
```

7. Based on the source code:

- a) How many function calls are needed to compute `fibonacci(3)`? Identify the value of the parameter `n` for each of these calls.

3 calls: n=3, n=2, n=1

- b) How many function calls are needed to compute `fibonacci(4)`? Identify the value of the parameter `n` for each of these calls.

5 calls: n=4, n=3, n=2, n=1, n=2

- c) How many function calls are needed to compute `fibonacci(5)`? Identify the value of the parameter `n` for each of these calls.

9 calls: n=5, n=4, n=3, n=2, n=1, n=2, n=3, n=2, n=1

8. Check your answers for the previous question by adding the following `print` statements to the code and rerunning the program:

- Insert `print("n is", n)` at Line 2, before the `# base case` comment
- Insert `print("fib({i}) is...")` at Line 10, before the `print` statement

9. What happens if you try to compute `fibonacci(0)` in the Python Shell?

The function is called with decreasing negative numbers until the Shell displays the error: "RuntimeError: maximum recursion depth exceeded while calling a Python object".

10. How could you modify the code so that this situation doesn't happen?

Add an `if` statement that returns `-1` if `n < 1`.

### Model 3 Summation

"In mathematics, summation (capital Greek sigma symbol:  $\Sigma$ ) is the addition of a sequence of numbers; the result is their sum or total."

$$\sum_{i=1}^{100} i = 1 + 2 + 3 + \dots + 100 = 5050$$

Source: <https://en.wikipedia.org/wiki/Summation>

11. Consider how to calculate  $\sum_{i=1}^4 i = 10$ .

a) Write out all the numbers that need to be added:

$$\sum_{i=1}^4 i = 1 + 2 + 3 + 4$$

b) Show how this sum can be calculated in terms of a smaller summation.

$$\sum_{i=1}^4 i = 4 + \sum_{i=1}^3 i$$

12. Write an expression similar to #11b showing how any summation of  $n$  integers can be calculated in terms of a smaller summation.

$$\sum_{i=1}^n i = n + \sum_{i=1}^{n-1} i$$

13. What is the base case of the summation? (Write the complete formula, not just the value.)

$$\sum_{i=1}^1 i = 1$$

Here are important questions to consider before writing a recursive function:

- How can you define the problem in terms of a smaller similar problem?
- What is the base case, where you solve an easy problem in one step?
- For the recursive call, how will you make the problem size smaller?

To avoid infinite recursion, make sure that each recursive call brings you closer to the base case!

14. Implement a recursive function named `summation` that takes a parameter `n` and returns the sum  $1 + 2 + \dots + n$ . It should only have an `if` statement and two `return` statements (no loops).

```
def summation(n):
    if n == 1:
        return 1
    else:
        return n + summation(n - 1)
```

15. Enter your code into a Python Editor, and test the function. Make sure that `summation(100)` correctly returns 5050.

16. Implement a recursive function named `geometric` that takes three parameters (`a`, `r`, and `n`) and returns the sum " $a + ar + ar^2 + ar^3 \dots$ " where  $n + 1$  is the total number of terms.

a) What is the base case?

`geometric(a, r, 0)` returns: `a`

b) What is the recursive case?

`geometric(a, r, n)` returns: `a * r ** n + geometric(a, r, n - 1)`

c) Write the function in Python:

```
def geometric(a, r, n):
    if n == 0:
        return a
    else:
        return a * r ** n + geometric(a, r, n - 1)
```

17. Enter your code into a Python Editor, and test the function. For example, if  $a = 10$  and  $r = 3$ , the first five terms would be 10, 30, 90, 270, and 810. Make sure that `geometric(10, 3, 4)` correctly returns 1210 (the sum of those five terms).

(demonstrate to instructor)